

WIRELESS Point-of-Sale


Endless Possibilities

The ExaDigm NX2200e wireless payment solution brings in the latest innovations in POS functionality over the largest wireless networks for fast-secure transactions, allowing for the utmost mobility while continuing to be fully compliant with payment industry standards.

- **SECURE**
Supports the latest industry standards
- **SCALABLE**
EMV & NFC support, including an optional camera
- **MOBILE**
Cellular & WiFi support; compact with a long operating battery life




CERTIFICATIONS



NX2200e

www.exadigm.com

NX2200e



Features & Benefits

Security - Built-in security transaction engine for the highest level of secure payment processing.

NFC Support - Improves customer experience by offering support for mobile wallet applications. Certified for both PayPass and PayWave.

EMV Support - ExaDigm has embraced future-proof strategies, such as EMV, to give you confidence and trust with every transaction.

Performance & Design - ExaDigm's multi-application platform allows for easy integration with other value-added applications, all in one device.

Accessories

Car Adapter - Charge your device from the accessory power outlet in your car with this universal car adapter.

Holster - The holster safeguards the NX2200e from the elements and is equipped with a belt clip and adjustable shoulder strap to secure the terminal comfortably on the user.

Li-Ion Battery - The removable battery provides long operating use without having to be recharged often.

Multi-Charger - ExaDigm's multi-charger comes with four battery charging bays, ensuring there is always a charged battery available.

Terminal Access Portal (TAP)

ExaDigm's Terminal Access Portal (TAP) provides the fastest, most secure and truly cost-effective remote device management tool for a wide range of users. Featuring a user-friendly interface, TAP can be accessed anytime, anywhere, ensuring real-time device management.

Specifications

Processor	ARM9, 32-bit secure processor
Memory	64 MB Flash, 128 MB SDRAM
Slots	4 PSAM card slots 1 SIM card slot 1 SIM/SD card slot
Card Readers	Contactless - ISO/IEC 14443 Magstripe - 3 track, bi-directional Smart card - ISO 7816
Display	3.2 inch color capacitive screen, 320 x 240
Keypad	10 operational keys, 2 functional keys
Audio	0.8W, mono
Thermal Printer	58mm x 40mm paper roll
Ports	1 Ethernet 1 Mini USB slave 1 USB host 1 proprietary host
PIN Pad	Internal, 3DES encryption, DUKPT key management
Communication	EVDO (CDMA), HSPA (GSM), Ethernet, WiFi (optional)
Size	L x W x H = 180 x 80 x 69mm
Weight	500g
Environment	Operating temperature: 0°C to 50°C (32°F to 122°F); humidity (non-condense): 10% to 90%; storage temperature: -20°C to 60°C (-4°F to 140°F); humidity (non-condense): 5% to 95%
Power Supply	Input: 100-240V, 50-60Hz Output: 8.5V/2.5A
Battery	Li-ion 1850mAh
Certifications	PCI PTS 4.x, PA-DSS 3.x, Paywave, Paypass, EMV Level 1 & 2
Optional	5MP camera 1D barcode scanner 2D QR code scanner Micro SD card support

