

Mobilize Your Enterprise*



Mobility Sales/Technical Center

1641 McGaw Avenue Irvine, CA 92614

- **o** 949.222.0300
- **T** 877.278.7860
- **F** 949.222.0375

Headquarters/Main Warehouse

2312 Touhy Avenue Elk Grove Village, IL 60007 **0** 847.818.1260 **T** 877.278.7860 **F** 847.818.1287

Infinite Peripherals Canada

677 MacDonald Avenue, Unit #210 Sault Ste Marie, ON P6B 1J4 Canada O 705.943.1808 E canada [at] ipcprint.com

ipcmobile.com

Specifications subject to change without notice. Infinite Peripherals, Mobilize Your Enterprise, Linea Pro, Infinea, Infinea Tab and Infinea Omni are trademarks of Infinite Peripherals, Inc. All other trademarks are the property of their respective owners.

 \odot 2016 Infinite Peripherals, Inc.

Infinea mPOS

GENERAL SPECIFICATIONS

FEATURES	
STANDARD FEATURES	2D Barcode Imager (with the ability to scan 1D barcodes), Li- ion Battery, Encrypted MSR (SRED PCI/PTS), EMV, NFC Payments, Lightning Connector
OPTIONAL FEATURES	None
MECHANICAL	
COMPATIBILITY	iPhone 5, 5S, SE or iPod touch 5th and 6th generation
DIMENSIONS (LxWxH)	145mm x 68mm x 27mm (5.7" x 2.7" x 1.1")
WEIGHT	188 grams (6.63 oz.) without iOS device
PORT	Mini USB for charge and sync

ELECTRICAL

BARCODE SCANNER (OPTIONAL)	2D high speed imager (supports all major 1D or 2D barcodes)	
BATTERY CAPACITY	Rechargeable Li-ion battery 3.7V / 1330mAh	
BATTERY LIFE	Over 10,000 scans and swipes per full charge	
CARD READER	3-track bidirectional Magnetic Stripe Reader (MSR)	
CONTACTLESS: NFC PAYMENTS (OPTIONAL)	• AMEX ExpressPay, MagStripe and EMV • Discover ZIP and D-PAS • MasterCard PayPass MagStripe and M/Chip • VISA PayWave MSD and qVSDC	
SMARTCARD READER	ISO7816, EMV L1 certified	
ENCRYPTION & KEY MANAGEMENT (OPTIONAL) 3DES, DUKPT		
INDICATOR	Visual: 4 LEDs for transaction and device status Audio: Electromagnetic buzzer	

CERTIFICATIONS

CERTIFICATIONS

Apple MFi, PCI PTS 3.x SRED (optional)

ENVIRONMENTAL

OPERATING ENVIRONMENT	Temperature: -10°C to +40°C (14°F to +104°F) Humidity: 5% to 90% RH
STORAGE ENVIRONMENT	Temperature: -20°C to +50°C (-4F to +122°F) Humidity: 5% to 90% RH